



WASTE MANAGEMENT PROGRAMME
GUIDELINES FOR THE RESPONSIBLE DISPOSAL OF
SPRAY TANK RINSE WATER
DECEMBER 2018 EDITION





PREVENT CROSS-CONTAMINATION OF SPRAY MIXTURES

1. It is likely that small quantities of pesticides may remain in spray tanks after spraying and it may contaminate follow-up spray mixtures with dire consequences for crop safety.
2. Cross contamination of spray mixtures may also cause failure of the pesticides to perform as expected.
3. Application equipment (spray equipment) must be thoroughly cleaned (sanitised) after each application, especially when herbicides were applied.
4. Visual inspection after sanitising is important to check for any residual precipitates that may be present even after thorough cleaning.
5. Always wear protective clothing when working with rinse (cleaning) agents.

BEST PRACTICE PROTOCOL

The spray tank must be thoroughly cleaned (sanitized) after spraying to prevent contamination of the new batch of spray mixture. It may require using a tank cleaning (rinse) agent, 5% sodium hypochlorite solution or a 20% aqueous ammonia solution especially after using hormonal herbicides.

- 1 Ensure the spray tank is totally emptied by spraying the last spray mixture out on the crop field in fallow areas. *Do not spray over crops* that have already been treated as overdosing will result in resistance development.
- 2 Add the required rinse agent according to its label instructions or if sodium hypochlorite is used, dilute 100ml 5% sodium hypochlorite in 10 liters fresh water as rinse agent. If ammonia is recommended on the product label as tank cleaning agent, follow those instructions; it is usually 1 liter aqueous ammonia per 100 liters water. Spray over the entire inner surface of the spray tank and leave for one hour.
- 3 Pump the rinsate out of the spray tank into a container. Dilute this ten-fold with fresh water and irrigate over fallow soil or onto a dirt road.
- 4 Rinse the spray tank properly with fresh water and spray the rinsate over fallow soil or onto a dirt road.
- 5 Repeat the rinse with fresh water and spray the rinsate over fallow soil or into a dirt road. Repeat the rinse with fresh water once more.

POST-SANITISING MAINTENANCE OF SPRAY TANKS AND ASSOCIATED EQUIPMENT

1	Check that all rinsate is out of the spray tank and drain pipes and nozzles fully.
2	Check all pipes for leaks and repair/replace if necessary.
3	Check all valves for leaks, lubricate and repair/replace if necessary.
4	Check pressure gauges and repair/replace if necessary.
5	Check nozzles, unblock if necessary and replace if worn out.
6	Check seals for leaks, lubricate and repair/replace if necessary.

CALIBRATE THE APPLICATION EQUIPMENT AT LEAST ONCE PER SEASON TO ENSURE THAT THE CORRECT DOSAGE IS APPLIED ACCORDING TO EVERY PESTICIDE'S LABEL INSTRUCTIONS. CALIBRATION IS AS MUCH PART OF MAINTENANCE AS SERVICING IS.